

GASSOFLEX SST



Aplicaciones

Gassoflex SST es recomendada para la impulsión y/o aspiración de una gran variedad de productos químicos altamente agresivos y es normalmente utilizada en aquellas aplicaciones en las que el polipropileno no es adecuado. Su forro interior en PTFE y sus espirales en Inoxidable la hacen ideal para el uso en camiones cisternas, vagones o en planta.

SST

Serie Standard: 10100

Serie Pesada: 14100

Construcción:

- Espiral Interior: Acero inoxidable 316 (S)
- Espiral Exterior: Acero inoxidable 316 (S)
- Forro Interior: P.T.F.E. (T)
- Cubierta: Polipropileno

Gama de Temperatura: -20°C a +100°C

Factor de Seguridad:

La presión de trabajo está basada en un factor de seguridad 5:1

Applications

Gassoflex SST is recommended for the delivery and/or suction of a wide range of highly aggressive chemical products and is used in applications where polypropylene is not appropriate. Its inner lining of PTFE and the stainless steel wire spirals make it ideal in use with cistern trucks, railcars or fixed deposits.

SST

Standard Series: 10100

Heavy Series: 14100

Construction:

- Inner Wire spiral: Stainless Steel 316 (S)
- Outer Wire spiral: Stainless Steel 316 (S)
- Inner Lining: P.T.F.E. (T)
- Cover: Polypropylene

Temperature range: -20°C a +100°C

Work Safety factor:

The working pressure is based on a safety factor of 5:1

Código Gassó Gassó code	Presión trabajo Working press.		Diámetro Diameter	Radio curvatura Curve radius	Peso Weight	Longitud máx. rollos Max. coil lengths
	(bar)	(PSI)				

GASSOFLEX 10100 SST

AIA625	10	150	1	68	0,85	35
—	10	150	1 1/4	74	1,07	35
AIA640	10	150	1 1/2	105	1,50	35
AIA650	10	150	2	190	2,00	35
AIA665	10	150	2 1/2	225	3,05	35
AIA680	10	150	3	290	3,55	35
AIA685	10	150	4	320	6,40	35

GASSOFLEX 14100 SST

—	14	210	1	68	0,85	35
—	14	210	1 1/4	74	1,07	35
—	14	210	1 1/2	105	1,50	35
—	14	210	2	190	2,00	35
—	14	210	2 1/2	225	3,05	35
—	14	210	3	290	3,55	35
—	14	210	4	320	6,40	35

CUSTOMIZE



Consultar otra configuración posible

Other configurations on request:

EEE, ESE, ...