

## WATERBLAST 30



<b>Inner Tube</b>	<b>Reinforcement</b>	<b>Cover</b>	
Synthetic rubber resistant to oils	4 high tensile steel spirals (up to size 20 mm) ; 6 high tensile steel spirals (size 25 mm)	Black synthetic rubber resistant to oils , weather agents and abrasion. MSHA approval upon request.	
<b>Specifications</b>	<b>Approvals</b>	<b>Applications</b>	<b>Temperature</b>
RAPISARDA		Waterblasting, Waterjetting, cleaning equipment	from -40°C (-40°F) to 100°C (212°F) Max 100°C (212°F)
<b>Recommended Fluids</b>		<b>Tolerances</b>	<b>Lengths</b>
Water, water emulsions		According to Rapisarda Specifications	Manufacturing coils
<b>Branding</b>		<b>Performances</b>	
<b>green /embossed:</b> RAPISARDA - WATERBLAST 30 SIZE x/x" - xxxxx PSI WP - xxxxx PSI BP ITALY <b>Reverse:</b> Q/Y -Production lot no.		High resistance to burst. Security factor : 2,5 :1	

I.D.				O.D.		Working Pressure		Burst Pressure		Actual Burst Pressure		Bending Radius		Weight	
Dn	dash	mm	inch	mm	inch	bar	psi	bar	psi	bar	psi	mm	inch	g/mt	lb/ft
6	0	6,4	1/4	17,8	0.700	850	12320	0	0	2200	31880	130	5,1	614	0,412
10	0	9,5	3/8	21,4	0.842	850	12320	0	0	2160	31300	155	6,1	784	0,526
12	0	12,7	1/2	24,5	0.964	850	12320	0	0	2200	31880	200	7,9	1020	0,684
20	0	19	3/4	32,8	1.291	850	12320	0	0	2360	34200	250	9,8	1930	1,295
25	0	25,4	1	44,6	1.756	850	12320	0	0	2250	32600	300	11,8	3350	2,247