

WATERBLAST 40



Inner Tube		Reinforcement		Cover	
Synthetic rubber resistant to oils		4 high tensile steel spirals for size 12 mm; 6 high tensile steel spirals for size 20 mm		Black synthetic rubber resistant to oils , weather agents and abrasion. MSHA approval upon request.	
Specifications		Approvals		Applications	
RAPISARDA				Waterblasting, Waterjetting, cleaning equipment	
				Temperature	
				from -40°C (-40°F) to 100°C (212°F) Max 100°C (212°F)	
Recommended Fluids				Tolerances	
Water, water emulsions				According to Rapisarda Specifications	
				Lengths	
				Manufacturing coils	
Branding				Performances	
green/embossed: RAPISARDA - WATERBLAST 40 SIZE x/x" - xxxx PSI WP - xxxxx PSI BP ITALY Reverse: Q/Y -Production lot no.				Very high resistance to burst. Security factor : 2,5 :1	

I.D.				O.D.		Working Pressure	Burst Pressure		Actual Burst Pressure		Bending Radius		Weight		
D	dash	mm	inc h	mm	inch	bar	psi	bar	ps i	bar	psi	mm	inc h	g/mt	lb/f t
12	0	12,7	1/2	27	1.063	1000	14490	0	0	2800	40580	200	7,87	1360	0,9 12
19	0	19	3/4	36	1.417	1000	14490	0	0	2800	40580	310	12,2	2500	1,6 77