

**WATERBLAST 45**



<b>Inner Tube</b>	<b>Reinforcement</b>	<b>Cover</b>	
Synthetic rubber resistant to oils	6 high tensile steel spirals	Black synthetic rubber resistant to oils , weather agents and abrasion. MSHA approval upon request.	
<b>Specifications</b>	<b>Approvals</b>	<b>Applications</b>	<b>Temperature</b>
RAPISARDA		Waterblasting, cleaning equipment	from -40°C (-40°F) to 100°C (212°F) Max 100°C (212°F)
<b>Recommended Fluids</b>		<b>Tolerances</b>	<b>Lengths</b>
Water, water emulsions		According to Rapisarda Specifications	Manufacturing coils
<b>Branding</b>		<b>Performances</b>	
<b>green/embossed:</b> RAPISARDA - WATERBLAST 45 SIZE x/x" - xxxxx PSI WP - xxxx PSI BP ITALY <b>Reverse:</b> Q/Y -Production lot no.		Very high resistance to burst. Security factor : 2,5 :1	

I.D.				O.D.		Working Pressure		Burst Pressure		Actual Burst Pressure		Bending Radius		Weight	
Dn	dash	mm	inch	mm	inch	bar	psi	bar	psi	bar	psi	mm	inch	g/mt	lb/ft
6	0	6,4	1/4	20,6	0.811	1200	17390	0	0	3300	47100	130	5,12	920	0,617
10	0	9,5	3/8	23,8	0.937	1200	17390	0	0	3200	45700	155	6,1	1120	0,751
12	0	12,7	1/2	29	1.141	1200	17390	0	0	3250	46400	230	9,05	1900	1,275