

## WATERBLAST 50



<b>Inner Tube</b>	<b>Reinforcement</b>	<b>Cover</b>			
Synthetic rubber resistant to oils	6 high tensile steel spirals	Black synthetic rubber resistant to oils , weather agents and abrasion. MSHA approval upon request.			
<b>Specifications</b>	<b>Approvals</b>	<b>Applications</b>	<b>Temperature</b>		
RAPISARDA		Waterblasting, cleaning equipment	from -40°C (-40°F)to 100°C (212°F) Max 100°C (212°F)		
<b>Recommended Fluids</b>		<b>Tolerances</b>	<b>Lengths</b>		
Water, water emulsions		According to Rapisarda Specifications	Manufacturing coils		
<b>Branding</b>				<b>Performances</b>	
<b>green/embossed:</b> RAPISARDA - WATERBLAST 50 SIZE x/x" - xxxxx PSI WP - xxxx PSI BP ITALY <b>Reverse:</b> Q/Y -Production lot no.				Very high resistance to burst. Security factor : 2,5 :1	

I.D.					O.D.		Working Pressure	Burst Pressure		Actual Burst Pressure		Bending Radius		Weight	
Dn	dash	mm	inch	mm	inch	bar	psi	bar	psi	bar	psi	mm	inch	g/mt	lb/ft
6	0	6,4	1/4	20,6	0.811	1400	20290	0	0	3550	51450	150	5,9	920	0,617
10	0	9,5	3/8	24	0.944	1400	20290	0	0	3550	51450	180	7,08	1370	0,92
12	0	12,7	1/2	29	1.141	1400	20290	0	0	3650	52900	230	9,05	1900	1,275